

Products Specification

Product name: 32inch Mobile Screen

Model: GK-32T-4K



***All information in this document is subject to the final interpretation of the manufacturer, all unauthorized and unauthorized copying is not recognized and should be prohibited. This document may not fully reflect all the latest changes in the product, the actual product shall be subject to the final version.**

Product Specification Version Log

Version	Date	Author	Description
V1.0	27-10-2025	Camellia Sun	Initial release

Function

- ◆ HD ten-point capacitive touch LCD
- ◆ Rotate vertically at 180°, automatic switch between landscape and portrait mode(90° left, 90° right).
- ◆ Supports 45° tilt adjustment (upward angle: 25°; compression angle: 20°).
- ◆ Adjustable height: 18cm.
- ◆ Simple tablet operation display interface.
- ◆ Wired/wireless screen projection.
- ◆ High-quality stereo speakers, output power can reach 8Ω 2×5W.
- ◆ Bases with omnidirectional wheels, move much easier.
- ◆ 192.4Wh Li-ion battery.
- ◆ Android 13.0 OS.
- ◆ Support HDMI, USB, Type-C interfaces.

Display

Size	32inch
Brand	Gaokeview
Resolution(pixels)	3840×2160 UHD
Brightness	250cd/m ² (Typ)
Colour Gamut	100%SRGB
Contrast Ratio	1000: 1 (Typ.)
Response Time	5ms
Life Time	50000h
Refreshing Frequency	60Hz
View Area(mm)	702*396.54

Size	32inch
Display Colors	16.7M colors

Motherboard

Chipset	RK3576	
CPU	Architecture	ARM Cortex A72*4+ARM Cortex A53*4
	Working Frequency	Max 4.0GHz
	Core	Octa-core
RAM	Standard: 8GB LPDDR4X	
ROM	Standard: 128GB	
OS	Android 14.0	
Power Supply	18V 6A / 19V 6.32A	
Batteries	15000mA/ 19V (192.4Wh)	
Audio Output Power	2×5W/8Ω	
Interface	HDMI*1, TYPE-C*1debug, USB 3.0*1, DC 5.5mm*1	

WIFI

Operating Frequency	2.4GHz/ 5.0GHz
WI-FI Standard	802.11AC/b/g/n
Bluetooth	4.2

TOUCH

Support ten-point capacitive touch

Camera & Mic

Camera	13MP AF Camera
--------	----------------

Camera	13MP AF Camera
Mic	Noise Canceling Mic 6050

Structure

Product Size(W x D x H)	733.76*430*1415.54mm
Package Size(W x D x H)	790*495*270mm

Accessories

Certificate of conformity	×1
Specification	×1
Warranty card	×1
Power Cable	×1
Universal wheel base	×1
Connecting Rod	×1
Screws	×1 set
Adapter	×1
Remote Controller	×1

Environment

- **Operating temperature 0°C ~ + 40°C**
- **Charging temperature 0°C ~ +45°C**
- **Operating humidity 0% ~ 65% RH Non-Condensing**
- **Storage humidity 0% ~ 60% RH Non-Condensing**
- **Operating altitude ≤3000m**