

Products Specification

Product name: 24inch Mobile Screen

Model: GK-24T



***All information in this document is subject to the final interpretation of the manufacturer, all unauthorized and unauthorized copying is not recognized and should be prohibited. This document may not fully reflect all the latest changes in the product, the actual product shall be subject to the final version.**

Product Specification Version Log

Version	Date	Author	Description
V1.0	08-12-2025	Camellia Sun	Initial release

Function

- ◆ HD ten-point capacitive touch LCD
- ◆ Rotate vertically at 180°, automatic switch between landscape and portrait mode(90° left, 90° right).
- ◆ Supports 45° tilt adjustment (upward angle: 25°; compression angle: 20°).
- ◆ Adjustable height: 20cm.
- ◆ Simple tablet operation display interface.
- ◆ Wired/wireless screen projection.
- ◆ High-quality stereo speakers, output power can reach 8Ω 2×5W.
- ◆ Bases with omnidirectional wheels, move much easier.
- ◆ 192.4Wh Li-ion battery.
- ◆ Android 13.0 OS.
- ◆ Support HDMI, USB, Type-C interfaces.

Display

Size	23.8inch
Brand	Gaokeview
Resolution(pixels)	1080×1920 FHD
Brightness	250cd/m ² (Typ)
Colour Gamut	100%SRGB
Contrast Ratio	1000: 1 (Typ.)
Response Time	6ms
Life Time	50000h
Refreshing Frequency	60Hz
View Area(mm)	521*299
Display Colors	16.7M colors

Motherboard

Chipset		MT6769(Optional 3576mainboard)
CPU	Architecture	ARM Cortex A75*2+ARM Cortex A55*6
	Working Frequency	Max 2.2GHz
	Core	Octa-core
RAM		Standard: 8GB LPDDR4X
ROM		Standard: 128GB
OS		Android 13.0
Power Supply		18V 6A / 19V 6.32A
Batteries		15000mA/ 192.4Wh
Audio Output Power		2×5W/4Ω
Interface		HDMI*1, TYPE-C*1debug, USB 2.0*1, DC 5.5mm*1

WIFI

Operating Frequency		2.4GHz/ 5.0GHz
WI-FI Standard		802.11AC/a/b/g/n
Bluetooth		5.0

TOUCH

Support ten-point capacitive touch	
------------------------------------	--

Camera & Mic

Camera		13MP AF Camera
Mic		Noise Canceling Mic 6050

Structure

Product Size(W x D x H)	562.4*430*1367.16mm
Package Size(W x D x H)	900*570*225mm

Accessories

Certificate of conformity	×1
Specification	×1
Warranty card	×1
Power Cable	×1
Universal wheel base	×1
Connecting Rod	×1
Screws	×1 set
Adapter	×1
Remote Controller	×1

Environment

- Operating temperature 0°C ~ + 40°C
- Charging temperature 0°C ~ +45°C
- Operating humidity 0% ~ 65% RH Non-Condensing
- Storage humidity 0% ~ 60% RH Non-Condensing
- Operating altitude ≤3000m